

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
6 May 2004 (06.05.2004)


PCT

(10) International Publication Number
WO 2004/038803 A1

- (51) International Patent Classification⁷: **H01L 27/146, H04N 3/15**
- (21) International Application Number: **PCT/GB2003/004613**
- (22) International Filing Date: **24 October 2003 (24.10.2003)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data:
0224770.8 24 October 2002 (24.10.2002) GB
- (71) Applicant (for all designated States except US): **COUNCIL FOR THE CENTRAL LABORATORY OF THE RESEARCH COUNCILS [GB/GB]; Rutherford Appleton Laboratory, Chilton, Didcot, Oxfordshire, OX11 0qx (GB).**
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **TURCHETTA, Renato, Andrea, Danilo [IT/GB]; Rutherford Appleton Laboratory, Chilton, Didcot, Oxfordshire, OX11 0QX (GB).**
- (81) Designated States (national): **AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.**
- (84) Designated States (regional): **ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).**
- Declaration under Rule 4.17:
— of inventorship (Rule 4.17(iv)) for US only
- Published:
— with international search report

[Continued on next page]

(54) Title: **IMAGING DEVICE**



(57) Abstract: An imaging device comprising a two-dimensional array of pixels which are scanned to build up a desired image. Each pixel comprises a sensor such as a photodiode PD which outputs a signal dependent upon the strength of the incident radiation. This signal is amplified in an inverter circuit MB1, MIN and switched by transistors MW1, MW2 which in turn are controlled by a write signal applied to their connected gate electrodes. During the write period, the output signal from photodiode PD is passed to a line (4) which is input to a number n+1 of memory cells M0 to Mn which are switched sequentially via respective control inputs sample to sample to receive and store respective samples of the amplified signal from photodiode PD. The stored samples are read out sequentially over a read period during which a read transistor MSE, controlled by a read signal at its gate electrode, connects the memory cells to an output terminal (3) connected to the column bus.

WO 2004/038803 A1

WO 2004/038803 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.